

IPC950

Fanless Industrial System with Intel® Core™ Processor i7/i5 or Celeron® Processor and Front Access I/O

Features

- Intel® Core™ i7/i5 processor (Tiger Lake U), 15W
- Flexible I/O module for further expansion
- M.2 Key E socket for wireless connection
- 2 DisplayPort
- Supports TPM 2.0
- Supports Intel® AMT
- 1 PCIe x4 slot
- Optional DIN-rail, bookshelf and wall mount



- | | |
|----------------------------|-------------------------------|
| 1. 4 x LED | 8. 8-CH DIO |
| 2. RS-232/422/485 | 9. Flexible System I/O Window |
| 3. 3 x LAN | 10. 4 x USB 3.1 (10G) |
| 4. Line-out | 11. 2 x DP++ |
| 5. Remote power switch | 12. 3-pin terminal block |
| 6. Switch for power on/off | 13. Ground terminal |
| 7. 3 x Antenna opening | 14. 1 x PCIe x4 slot |



Specifications

Standard Color	Silver & black	
Construction	Aluminum extrusion heavy-duty cold-rolled steel	
Processor System	CPU Level	Intel® Core™ i7-1185G7E/i5-1145G7E & Intel® Celeron® 6305E processor (Tiger Lake U), 15W
	Chipset	SoC integrated
System Memory	2 x DDR4-3200 MT/s un-buffered SO-DIMM, up to 64GB	
System I/O	Ethernet	1 x 10/100/1000/2500 Mbps Ethernet (Intel® I225-LM) 2 x 10/100/1000 Mbps Ethernet (Intel® I210-AT)
	Serial	1 x RS-232/422/485 (default RS-232, BIOS selection)
	DIO	Programmable 8-CH DIO via 10-pin terminal block, TTL type
	USB	4 x USB 3.1 (10G) Type A 1 x Internal USB 2.0 for license key usage, up to 20mm
	Display	2 x DisplayPort++ 1.2 4K; support resolution up to 4096 x 2160 @60HZ
	Audio	1 x Line-out
	Others	1 x Switch for power on/off with LED (ATX) 1 x Remote switch 1 x 3-pin terminal block 1 x AT/ATX selectable switch
	Flexible System I/O Module	AX93511
AX93512		2 x RS-232/422/485 with isolated 1.5kVDC & 8-in/8-out with isolated 1.5kVDC DIO module
AX93516		4 x RS-232/422/485 with isolated 2kVDC module
AX93519		1 x 10/100/1000 Mbps Ethernet, 2 x RS-232/422/485 and 2 x USB 2.0 module
Blank I/O cover (default)		
TPM	TPM 2.0	

Expansion Interface	M.2 Key E 2230 socket
	SIM 1 x SIM slot
	mPCIe 1 x Full-size PCI Express Mini Card slot (USB & PCIe interface)
PCIe	1 x PCIe x4 slot for Axiomtek I/O card (optional)
	• AX92320: 2/4-port GigE PoE LAN PCI Express card (max. 100W PoE power output)
	• AX92321: 4-port/8-port USB 3.0 PCI Express card with 4 independent host controllers
	• AX92322: 2-port/4-port GbE LAN PCI Express card
	• AX92351: 32-CH isolated digital I/O with digital filter
Storage	1 x 2.5" HDD/SSD bay (7/9.5 mm height)
	1 x M.2 Key B+M 2280 socket (SATA interface) for SSD
System Indicators	1 x CPU status LED
	1 x Programmable (GPIO) LED
	1 x HDD/SSD access LED
	1 x Power LED
Power Input	Type: ATX/AT
	Input: 24 VDC (uMin=19V/uMax=30V)
Operating Temperature	-20°C to +50°C (-4°F to +122°F) with W.T. SSD
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Relative Humidity	10% to 95% (non-condensing)
Dimensions	69.5 mm (2.73") (W) x 225 mm (8.85") (H) x 230 mm (9") (D)
Weight (net/gross)	4 kg/6 kg
Certifications	CE (EN 61000-6-4/EN 61000-6-2), FCC

Ordering Information

System	
IPC950-11i7-F5 (P/N: E26G950101)	Fanless industrial system with Intel® Core™ i7-1185G7E and blank flexible I/O, w/o Axiomtek logo
IPC950-11i5-F5 (P/N: E26G950102)	Fanless industrial system with Intel® Core™ i5-1145G7E and blank flexible I/O, w/o Axiomtek logo
IPC950-11i7-F5E1 (P/N: E26G950105)	Fanless industrial system with Intel® Core™ i7-1185G7E, blank flexible I/O, and 1 PCIe x4 slot, w/o Axiomtek logo

Optional Flexible System I/O Module

AX93511 (P/N: 886G95010A0E)	4 x RS-232/422/485 module (default RS-232)
AX93512 (P/N: 886G95011A0E)	2 x RS-232/422/485 with isolated 1.5kVDC & 8-in/8-out with isolated 1.5kVDC DIO module
AX93516 (P/N: 886G95012A0E)	4 x RS-232/422/485 with isolated 2kVDC module
AX93519 (P/N: 886G95013A0E)	1 x 10/100/1000 Mbps (Intel® I210-AT) Ethernet, 2 x RS-232/422/485 & 2 x USB 2.0

Optional

2.5" SATA HDD/SSD	
M.2 Key B+M 2280 (SATA) NVMe SSD	
DDR4-3200 MT/s un-buffered SO-DIMM, up to 64GB	
886G95018A0E	DIN-rail mounting kit for IPC950 system
886G9501AA0E	DIN-rail mounting kit for IPC950 w/PCIe x4 slot system
886G95019A0E	Bookshelf mounting kit for IPC950 system
886G9501BA0E	Bookshelf mounting kit for IPC950 w/PCIe x4 slot system
886G9501EA0E	Wall mounting kit for IPC950 and IPC950 w/PCIe x4 slot system
59492350700E	Power cable for AX92320
509000001500	Adaptor 24V/120W, wire only

Power Protection

DC Version

OVP (over voltage protection)
 OCP (over current protection)
 Reverse Protection

Packing List

1 x IPC950 unit
 1 x Screw pack
 1 x Terminal block
 1 x Remote power switch cable
 3 x Antenna isolated washer

Dimensions

